

Constructional and Electrical Performance Data
3192Y – Ordinary Duty Flexible Cords (Flat)



AEI Cables Limited

Construction	Flexible plain annealed copper conductors, Polyvinyl Chloride (PVC) insulation, cores laid flat, Polyvinyl Chloride (PVC) sheath		
Specification	BS6500 Table 26	Voltage Rating	0.3/0.3 kV
Operating Temperature	0°C (Min) to 60°C (Max)		
Standard Colours	2 core : Blue & Brown Sheath : White		
Harmonised Code	H05VVH2-F		
Approvals	BASEC Schedule No. 024/001/176		

No. of cores & Nominal Cross Sectional Area of Conductor	Current Rating*		Voltage Drop*			Maximum DC Conductor Resistance @ 20°C	Nominal Overall Diameter	Nominal Weight	AEI Product Code
	2 Core Single Phase ac	3 Core Three Phase ac	2 Core dc	2 Core Single Phase ac	3 Core Three Phase ac				
no x mm ²	Amps	Amps	mV/A/M	mV/A/M	mV/A/M	Ω/Km	mm	Kg/Km	
2 x 0.75	6.00	-	62.00	62.00	-	26.00	4.20 x 6.60	47.00	232-440

* The current rating and voltage drop factors are extracted from Appendix 4 of BS7671, Requirements for Electrical Installations: IEE Wiring Regulations Sixteenth Edition, table 4H3A.

General Note
 AEI Cables reserves the right to amend the product information without notice or liability.
 The information is considered accurate at the time of going to print.

© AEI Cables Limited Durham Road, Birtley, Chester-le-Street, County Durham DH3 2RA

Telephone: +44 (0) 191 410 3111 Facsimile: +44 (0) 191 410 8312
 Email: sales@aeicables.co.uk or technical@aeicables.co.uk
 Website: www.aeicables.co.uk



A subsidiary of TT electronics plc