



## Commando Combi Units offer RCD protection in hazardous environments

They are enclosed in PBT boxes for protection against high impact and are available in IP44 (Splashproof) or IP67 (Watertight) making Commando Combination Units some of the safest products available

INGRESS PROTECTED

## COMMANDO COMBINATION UNITS



**IP 44  
SPLASHPROOF  
100 - 130V  
50 - 60 Hz**

### SOCKET OUTLETS

SINGLE  
PRE-WIRED WITH  
30mA RCD

TWIN  
PRE-WIRED WITH  
30mA RCDs  
*INDIVIDUALLY PROTECTED*

TRIPLE  
PRE-WIRED WITH  
SINGLE  
30mA RCD



| Amps | Pin Configuration | Earth Hour Pos |
|------|-------------------|----------------|
| 16   | 2P+E              | 4              |
| 32   | 2P+E              | 4              |

| Amps | Pin Configuration | Earth Hour Pos | Model             | Model             | Model             |
|------|-------------------|----------------|-------------------|-------------------|-------------------|
| 16   | 2P+E              | 4              | <b>K13413 YEL</b> | <b>K13173 YEL</b> | <b>K13193 YEL</b> |
| 32   | 2P+E              | 4              |                   |                   |                   |

Suitable for top entry 2 x 25mm

Suitable for top entry 2 x Ø25 / 2 x Ø38  
Bottom entry 3 x 47.5mm

Suitable for top entry 2 x Ø25 / 2 x Ø38  
Bottom entry 3 x 47.5mm

**IP44  
SPLASHPROOF  
200 - 250V  
50 - 60 Hz**

### SOCKET OUTLETS

SINGLE  
PRE-WIRED WITH  
30mA RCD

TWIN  
PRE-WIRED WITH  
30mA RCDs  
*INDIVIDUALLY PROTECTED*

TRIPLE  
PRE-WIRED WITH  
SINGLE  
30mA RCD



| Amps | Pin Configuration | Earth Hour Pos |
|------|-------------------|----------------|
| 16   | 2P+E              | 6              |
| 32   | 2P+E              | 6              |
| 63   | 2P+E              | 6              |

| Amps | Pin Configuration | Earth Hour Pos | Model              | Model             | Model             |
|------|-------------------|----------------|--------------------|-------------------|-------------------|
| 16   | 2P+E              | 6              | <b>K13414 BLU</b>  | <b>K13174 BLU</b> | <b>K13194 BLU</b> |
| 32   | 2P+E              | 6              | <b>K13433 BLU</b>  | <b>K13184 BLU</b> |                   |
| 63   | 2P+E              | 6              | <b>K13463 BLU*</b> |                   |                   |

16/32A Suitable for top entry 2 x 25mm.  
63A Suitable for top entry 2 x Ø25/2 x Ø38. Bottom entry 3 x 47.5mm

Suitable for top entry 2 x Ø25 / 2 x Ø38  
Bottom entry 3 x 47.5mm

Suitable for top entry 2 x Ø25 / 2 x Ø38  
Bottom entry 3 x 47.5mm

**IP 44  
SPLASHPROOF  
380 - 415V  
50 - 60 Hz**

### SOCKET OUTLETS

SINGLE  
PRE-WIRED WITH  
30mA RCD

TWIN  
PRE-WIRED WITH  
30mA RCDs  
*INDIVIDUALLY PROTECTED*

\*these list numbers are constructed as twin and triple units. See page 328

| Amps | Pin Configuration | Earth Hour Pos |
|------|-------------------|----------------|
| 16   | 3P+E              | 6              |
| 16   | 3P+N+E            | 6              |
| 32   | 3P+E              | 6              |
| 32   | 3P+N+E            | 6              |
| 63   | 3P+E              | 6              |
| 63   | 3P+N+E            | 6              |



| Amps | Pin Configuration | Earth Hour Pos | Model              | Model             | Model |
|------|-------------------|----------------|--------------------|-------------------|-------|
| 16   | 3P+E              | 6              | <b>K13415 RED</b>  | <b>K13175 RED</b> |       |
| 16   | 3P+N+E            | 6              | <b>K13416 RED</b>  | <b>K13176 RED</b> |       |
| 32   | 3P+E              | 6              | <b>K13434 RED</b>  | <b>K13185 RED</b> |       |
| 32   | 3P+N+E            | 6              | <b>K13435 RED</b>  | <b>K13186 RED</b> |       |
| 63   | 3P+E              | 6              | <b>K13464 RED*</b> |                   |       |
| 63   | 3P+N+E            | 6              | <b>K13465 RED*</b> |                   |       |

16/32A Suitable for top entry 2 x 25mm  
63A Suitable for top entry 2 x Ø25/2 x Ø38. Bottom entry 3 x 47.5mm

Suitable for top entry 2 x Ø25 / 2 x Ø38  
Bottom entry 3 x 47.5mm



TECHNICAL HOTLINE +44 (0)1268 563720

INGRESS PROTECTED

ANGLED  
TWIN  
SURFACE  
PRE-WIRED



**K13143 YEL**

Suitable for top entry  
2 x Ø25 / 2 x Ø38 Bottom  
entry 3 x 47.5mm

ANGLED  
TWIN  
SURFACE  
UNWIRED



**K13043 YEL**

Suitable for top entry  
2 x Ø25 / 2 x Ø38  
Bottom entry 3 x 47.5mm

**SWITCHSOCKET  
OUTLET**  
INTERLOCKED  
PRE-WIRED WITH  
30mA RCD



**K13309 YEL**  
**K13342 YEL**

Suitable for top entry 2 x Ø25

**IP 67  
WATERTIGHT**  
**100 - 130V**  
**50 - 60 Hz**

**SOCKET OUTLET**  
SINGLE  
PRE-WIRED WITH  
30mA RCD



**K13713 YEL**

Suitable for top entry 2 x Ø25

**SWITCHSOCKET  
OUTLET**  
INTERLOCKED  
PRE-WIRED WITH  
30mA RCD



**K13346 YEL**  
**K13347 YEL**

Suitable for top entry 2 x Ø25

| Amps | Pin Configuration | Earth Hour Pos |
|------|-------------------|----------------|
| 16   | 2P+E              | 4              |
| 32   | 2P+E              | 4              |

ANGLED  
TWIN  
SURFACE  
PRE-WIRED



**K13144 BLU**

Suitable for top entry  
2 x Ø25 / 2 x Ø38  
Bottom entry 3 x 47.5mm

ANGLED  
TWIN  
SURFACE  
UNWIRED



**K13044 BLU**

Suitable for top entry  
2 x Ø25 / 2 x Ø38  
Bottom entry 3 x 47.5mm

**SWITCHSOCKET  
OUTLET**  
INTERLOCKED  
PRE-WIRED WITH  
30mA RCD



**K13310 BLU**  
**K13343 BLU**

Suitable for top entry 2 x Ø25

**IP 67  
WATERTIGHT**  
**200 - 250V**  
**50 - 60 Hz**

**SOCKET OUTLET**  
SINGLE  
PRE-WIRED WITH  
30mA RCD



**K13714 BLU**  
**K13733 BLU**

Suitable for top entry 2 x Ø25

**SWITCHSOCKET  
OUTLET**  
INTERLOCKED  
PRE-WIRED WITH  
30mA RCD



**K13348 BLU**  
**K13349 BLU**

Suitable for top entry 2 x Ø25

| Amps | Pin Configuration | Earth Hour Pos |
|------|-------------------|----------------|
| 16   | 2P+E              | 6              |
| 32   | 2P+E              | 6              |

Suitable for top entry  
2 x Ø25 / 2 x Ø38  
Bottom entry 3 x 47.5mm

Suitable for top entry  
2 x Ø25 / 2 x Ø38  
Bottom entry 3 x 47.5mm

**SWITCHSOCKET  
OUTLET**  
INTERLOCKED  
PRE-WIRED WITH  
30mA RCD



**K13311 RED**  
**K13312 RED**  
**K13344 RED**  
**K13345 RED**

Suitable for top entry 2 x Ø25

**IP 67  
WATERTIGHT**  
**380 - 415V**  
**50 - 60 Hz**

**SOCKET OUTLET**  
SINGLE  
PRE-WIRED WITH  
30mA RCD



**K13715 RED**  
**K13716 RED**  
**K13734 RED**  
**K13735 RED**

Suitable for top entry 2 x Ø25

**SWITCHSOCKET  
OUTLET**  
INTERLOCKED  
PRE-WIRED WITH  
30mA RCD



**K13350 RED**  
**K13351 RED**  
**K13352 RED**  
**K13353 RED**

Suitable for top entry 2 x Ø25

| Amps | Pin Configuration | Earth Hour Pos |
|------|-------------------|----------------|
| 16   | 3P+E              | 6              |
| 16   | 3P+N+E            | 6              |
| 32   | 3P+E              | 6              |
| 32   | 3P+N+E            | 6              |



Spacer feet can be used  
on wall mounted units  
for cleaning access