



SWITCHSOCKET OUTLETS


13 AMP
FLUSH



K5357 PBS



K5357 PBS CB



K5347 PBS



K5347 PBS B

Understated style in solid brass consisting of an extensive range of accessories with a crisp, plain edge

The highly polished, wet lacquered finish is durable, luxurious and tarnish resistant, making it ideal for hotels, offices, public buildings and domestic housing

- K5357 PBS** 1
- K5357 PBS B** 1
- K5357 PBS CB** 1
- 1 GANG DP 13 AMP
DUAL EARTH TERMINALS
- K5347 PBS** 1
- K5347 PBS B** 1
- K5347 PBS CB** 1
- 2 GANG DP 13 AMP

MOUNTING BOXES

FLUSH 25mm

1 gang: 861 ZIC,
2 gang: 862 ZIC

FLUSH 35mm (for extra wiring space)

1 gang: 866 ZIC,
2 gang: 886 ZIC

High integrity earthing. K5357 is fitted with two earth terminals to provide a double earth facility when installations are to comply with Regulation 607 of BS.7671, IEE Wiring Regulations

DIMENSIONS:

1 gang: 87.5 x 87.5mm
2 gang: 87.5 x 149.5mm

FIXING CENTRES:

1 gang: 60.3mm
2 gang: 120.6mm

BS.1363 Pt. 2: 1995

DECORATIVE

SWITCHSOCKET
OUTLETS

13 AMP
NON STANDARD
15 AMP
FLUSH

240V a.c., 50Hz
RCD PROTECTED
13 AMP
FLUSH

SOCKET
OUTLETS

2 AMP, 5 AMP AND
15 AMP
FLUSH

16 AMP
MODULAR FORMAT
FLUSH

SHAVER
SUPPLY
UNITS

K1278 PBS



K1278 PBS B



K5383 PBS



K5383 PBS CB



K6307 PBS



K5380 PBS



K5381 PBS B



K5481 PBS



K5482 PBS



K5092 PBS / K4950 WHI



K5092 PBS / K4950 BLK



K5331 PBS / K4901 WHI



K5331 PBS / K4901 BLK



K4404 PBS



K4410 PBS B

K1278 PBS
K1278 PBS B
K1278 PBS CB

1 GANG DP 13 AMP
NON STANDARD
WITH CLEAN EARTH FACILITY

K5383 PBS
K5383 PBS B
K5383 PBS CB

1 GANG DP 15 AMP

MOUNTING BOXES

FLUSH 25mm
861 ZIC
FLUSH 35mm (for extra wiring space)
866 ZIC

K1268 has facility for 'clean earth'
connection and is suitable for non-
standard plugs with 'T' shaped earth
pins.

DIMENSIONS:
87.5 x 87.5mm
FIXING CENTRES:
60.3mm
BS.1363 Pt. 2: 1995 (13A)
BS.546: 1950 (15A)

1
1
1

K6307 PBS

1 GANG
30MA RATED TRIPPING CURRENT
ACTIVE CONTROL CIRCUIT

B suffix on the list number
denotes BLACK INSERTS
C denotes METAL ROCKER CAP

MOUNTING BOXES

FLUSH: 886 ZIC
Boxes must have a minimum depth
of 35mm

K6307 is pulsating d.c. and a.c.
fault current sensitive
Only suitable for supply voltage of
230-240V a.c., 50Hz.

DIMENSIONS: 87.5 x 149.5mm

FIXING CENTRES:
120.6mm BS.7288: 1990

K5357, K5347, BS1363 Pt 2: 1995
K5383 BS.5546: 1950
K1278 BS.1363 Pt 2: 1995
(where relevant)

1

K5380 PBS
K5380 PBS B

2 AMP SHUTTERED

K5381 PBS
K5381 PBS B

5 AMP SHUTTERED

K5481 PBS
K5481 PBS B

1 GANG SHUTTERED
15 AMP 127V
(NON EU)

K5482 PBS
K5482 PBS B

2 GANG SHUTTERED
15 AMP 127V
(NON EU)

MOUNTING BOXES

FLUSH 25mm
1 gang: 861 ZIC
2 gang: 862 ZIC

FLUSH 35mm
(for extra wiring space)
1 gang: 866 ZIC
2 gang: 886 ZIC

DIMENSIONS:
1 gang: 87.5 x 87.5mm
2 gang: 87.5 x 149.5mm
FIXING CENTRES: 1 gang: 60.3mm
2 gang: 120.6mm

BS.546: 1950 (Round Pin)
SSA 444: 1985 (15A 127V)

1
1

1
1

1
1

1
1

K5092 PBS with
K4950 WHI/BLK
and K3702 Grid

1 GANG 16 AMP 250V
SHUTTERED GERMAN TYPE
(2P+E) SOCKET
(NON UK)

K5094 PBS with
2 X K4950 WHI/BLK
and K3704 Grid

2 GANG 16 AMP 250V
SHUTTERED GERMAN TYPE
(2P+E) SOCKETS

K5331 PBS with
K4901 WHI/BLK
and K3701 Grid

1 GANG 16 AMP 125/250V
SHUTTERED
UNIVERSAL SOCKET

2P+E SOCKETS

MOUNTING BOXES
FLUSH 35mm:
1 GANG: 866 ZIC/2 GANG: 886 ZIC
DIMENSIONS: 1 gang: 87.5 x 87.5mm
2 gang: 87.5 x 149.5mm

IEC884-1:1994

UNIVERSAL
BS.5733: 1995
MOUNTING BOX
Flush 35mm 866 ZIC
DIMENSIONS: 87.5 x 87.5

The universal socket does not incorporate an
earth contact. Therefore, appliances needing
earth connection (class 1 equipment) must NOT
be used with this socket. The socket is intended
for use with BS, USA and CEE standard plugs.

1
1
10

1
1
10

1
10
10

K4404 PBS
K4404 PBS B

DUAL VOLTAGE
115/230 VOLT OUTPUT
(220/240 VOLT
50/60HZ INPUT)

K4410 PBS
K4410 PBS B

DUAL VOLTAGE
115/230 VOLT OUTPUT
(120/130 VOLT
50/60HZ INPUT)
(NON UK)

MOUNTING BOXES

FLUSH: 878 ZIC

This design incorporates a double
wound isolating transformer rated
20VA at 230 or 115 volts it meets
BS.3535: 1996 making it safe for
use in bathrooms. Insertion of a
shaver plug automatically switches
on by energising the primary side
of the isolating transformer –
removal automatically switches off.
The transformer is protected against
overload by an automatic solid
state overload device with
automatic resetting.

DIMENSIONS: 149.5 x 87.5mm

FIXING CENTRES: 120.6mm

BS.3535: 1996

1
1

1
1

1
10
10

CONNECTION UNITS

FLUSH

DP SWITCHES

32 AMP AND
45 AMP
FLUSH

COOKER SWITCHES

45 AMP
DP MAIN SWITCH
AND 13 AMP
SWITCH SOCKET
OUTLET WITH
NEONS

TV/FM COAXIAL AND SATELLITE SOCKET OUTLETS

FLUSH

PLATESWITCHES

10 AMP
FLUSH

10 AMP
WIDE ROCKER
FLUSH



K5361 PBS



K5361 PBS B



K5971 PBS



K5971 PBS B



K5305 PBS



K5336 PBS



K5336 PBS B



K5261 PBS



K5261 PBS B



K5320 PBS



K5322 PBS B



K5322 PBS



K5325 PBS



K5371 PBS CB



K5371 PBS



K5372 PBS B



K5373 PBS



K5731 PBS



K5731 PBS B



K5732 PBS



K5732 PBS B

K5361 PBS **1**
K5361 PBS B **1**
DP SWITCHED
WITH NEON

K5971 PBS **1**
K5971 PBS B **1**
DP SWITCHED
WITH FLEX OUTLET
AND NEON

K5305 PBS **1**
K5305 PBS B **1**
32 AMP DP SWITCH
WITH NEON

K5336 PBS **1**
K5336 PBS B **1**
45 AMP DP SWITCH
WITH NEON

K5261 PBS **1**
K5261 PBS B **1**
COOKER SWITCH

K5320 PBS **1**
K5320 PBS B **1**
SINGLE OUTLET
(NON ISOLATED)

K5321 PBS **1**
K5321 PBS B **1**
SINGLE OUTLET
(ISOLATED)

K5322 PBS **1**
K5322 PBS B **1**
TWIN OUTLET WITH
FM/TV DIPLEXER (ISOLATED)

K5325 PBS **1**
K5325 PBS B **1**
SINGLE OUTLET F TYPE
SATELLITE SOCKET

K5371 PBS CB **1**
K5371 PBS **1**
K5371 PBS B **1**
1 GANG SP
TWO WAY

K5372 PBS **1**
K5372 PBS B **1**
2 GANG SP
TWO WAY

K5379 PBS CB **1**
2 GANG SP
TWO WAY WITH SEPARATE
SWITCHES

K5373 PBS **1**
K5373 PBS B **1**
3 GANG SP
TWO WAY

K5731 PBS **1**
K5731 PBS B **1**
1 GANG SP
TWO WAY
WIDE ROCKER

K5732 PBS **1**
K5732 PBS B **1**
2 GANG SP
TWO WAY
WIDE ROCKER

MOUNTING BOXES
FLUSH:
866 ZIC

All units are fitted with a
13amp fuse (to BS.1362)

TERMINAL CAPACITY
2 x 6mm² stranded (max)

DIMENSIONS:
87.5 x 87.5mm
FIXING CENTRES:
60.3mm
BS. 1363 Pt 4: 1995

MOUNTING BOXES

K5305 FLUSH:
866 ZIC (6mm² conductors)
877 ZIC (10mm² conductors)

K5336 FLUSH:
886 ZIC (6mm² conductors)
878 ZIC (10mm² conductors)
Fitted with an earth terminal.

These products are not
recommended for switching
large banks of PCs

DIMENSIONS:
5305: 87.5 x 87.5mm
5336: 87.5 x 149.5mm

FIXING CENTRES:
5305: 60.3mm
5336: 120.6mm

BS.3676 Pt.1: 1989

MOUNTING BOXES

FLUSH:
886 ZIC
(Up to 6mm² conductor)
878 ZIC
(Up to 10mm² conductor)

DIMENSIONS:
86 x 146mm

FIXING CENTRES:
120.6mm

BS.4177: 1992

MOUNTING BOXES
FLUSH: 861 ZIC

K5320 K5325 Single outlet for
connection to a single TV or FM co-axial
aerial lead.

K5321, K5322 Provides safety isolation
rated at 2000Va.c. between aerial lead
and socket. Single outlet for connection
to a single TV or FM co-axial aerial lead.
Twin outlet with TV/FM diplexer for
connection to single co-axial aerial lead
with combined TV & FM signals. Suitable
for UHF TV and VHF FM radio.

DIMENSIONS: 87.5 x 87.5mm
FIXING CENTRES: 60.3mm
IEC169-2: 1965 BS. 5733: 1995 where
applicable

MOUNTING BOXES
FLUSH: 3995 ZIC

These switches do not have to be derated when
used with fluorescent or inductive loads. Switches
can be wired as either one-way or two-way. Note:
Replacement for 5375 PBS intermediate switch use
K4893 WHI
20A intermediate switch module, K5331 PBS grid
plate and K3701 grid.

DIMENSIONS:
87.5 x 87.5mm
FIXING CENTRES:
60.3mm
BS.3676 Pt.1: 1989

Fully screened modular TV/satellite outlets are also
available to fit Euro frontplates. See page 157

B suffix on the list number
denotes BLACK INSERTS
C denotes METAL ROCKER
CAP

DECORATIVE

DIMMER SWITCHES

230V a.c. 50Hz
TUNGSTEN FILAMENT
FLUSH

230V a.c. 50Hz
TUNGSTEN FILAMENT
AND LOW VOLTAGE
FLUSH

DIMMER SWITCHES (NON UK)

200-240V a.c.
50Hz & 60Hz
FLUSH

127V a.c. 60Hz
FLUSH

BLANK PLATES

FLUSH



K5306 PBS



K5306 PBS LV



K1531 PBS



K1731 PBS



K5330 PBS



K5307 PBS




K5307 PBS LV




K1561 PBS



K1741 PBS



K5329 PBS



K5308 PBS



K5301 PBS LV



K1641 PBS



K1761 PBS



K5301 PBS



K5302 PBS LV



K1661 PBS

- K5306 PBS** 1 1
1 GANG TWO WAY SINGLE
40W min, 250W max
- K5307 PBS** 1 1
1 GANG TWO WAY DOUBLE
40W min, 250W max for each dimmer
- K5308 PBS** 1 1
2 GANG TWO WAY TRIPLE
40W min, 250W max for each dimmer
- K5301 PBS** 1 1
1 GANG TWO WAY SINGLE
75W min, 500W max
- K5302 PBS** 1 1
2 GANG TWO WAY DOUBLE
60W min, 450W max for each dimmer

- K5306 PBS LV** 1 1
1 GANG TWO WAY SINGLE
40W/VA min, 300W/240VA max
- K5307 PBS LV** 1 1
1 GANG TWO WAY DOUBLE
40W/VA min, 300W/240VA max for each dimmer
MIN. BOX DEPTH - 35mm
- K5301 PBS LV** 1 1
1 GANG TWO WAY SINGLE
60W/VA min, 500W/400VA max
- K5302 PBS LV** 1 1
2 GANG TWO WAY DOUBLE
60W/VA min, 450W/360VA max for each dimmer

- K1531 PBS** 1 1
1 GANG SINGLE
ONE WAY 40-250W 50HZ
- K1541 PBS** 1 1
1 GANG SINGLE
ONE WAY 75-500W 50HZ
- K1561 PBS** 1 1
1 GANG SINGLE
TWO WAY 100-1000W 50HZ
- K1631 PBS** 1 1
1 GANG SINGLE
ONE WAY 40-250W 60HZ
- K1641 PBS** 1 1
1 GANG SINGLE
ONE WAY 75-500W 60HZ
- K1661 PBS** 1 1
1 GANG SINGLE
TWO WAY 100-1000W 60HZ

- K1731 PBS** 1 1
1 GANG SINGLE
ONE WAY 40-250W
- K1741 PBS** 1 1
1 GANG SINGLE
TWO WAY 60-450W
- K1761 PBS** 1 1
2 GANG SINGLE
TWO WAY 90-650W

- K5330 PBS** 1 1
1 GANG
- K5329 PBS** 1 1
2 GANG

Conforming to the latest standards BS EN 60669-2-1 and BS EN 55015, they are overload protected and are suitable for use with tungsten filament lamps only.
Two way dimmers use push on/push off switches.
They are not suitable for use with fluorescent loads or with electronic or wire-wound transformers in low voltage lighting systems

Conforming to the latest standards BS EN 60669-2-1 and BS EN 55015, they use 'state of the art' micro controller based circuitry to provide soft start and overload protection.
The soft start feature helps in greatly prolonging the life of tungsten, normal or halogen lamps.
Suitable for use with tungsten filament GLS lamps and low voltage halogen lamps via good quality dimmable electronic or wire-wound low voltage transformers.
Not suitable for use with fluorescent loads.

MOUNTING BOXES FOR DIMMERS	
FLUSH:	1 gang: 861 ZIC 25mm deep min
	866ZIC - 35mm deep min for K5307 PBS LV
	2 gang: 862 ZIC 25mm deep min
DIMENSIONS:	1 gang: 86 x 86mm
	2 gang: 86 x 146mm
FIXING CENTRES:	1 gang: 60.3mm
	2 gang: 120.6mm

Conforming to relevant parts of BS 5518, these dimmers are suitable for use with tungsten filament lamps only.
NOTE: Dimmer switches specified to work at 50Hz are not really suitable for use at 60Hz and vice versa.
The one way dimmers use rotary on/off switches, while the two way dimmers use push on/push off switches.
These dimmer switches are not suitable for use with fluorescent loads, electronic or wire-wound transformers in low voltage lighting systems

DIMENSIONS:
1 gang: 87.5 x 87.5mm
2 gang: 87.5 x 149.5mm
FIXING CENTRES:
1 gang: 60.3mm
2 gang: 120.6mm
BS. 5733: 1995

**TELEPHONE
SOCKET OUTLET**
**EURO DATA
FRONTPLATES**
**LJU6C DATA
FRONTPLATES**
**MK MODULAR
DATA,
FRONTPLATES**
**GRID PLUS
FRONTPLATES**

FLUSH

FLUSH

FLUSH

FLUSH


FLUSH



K5340 PBS




K5340 PBS B




K182 PBS




K184 PBS



K172 PBS



K5091 PBS



K5092 PBS




K5093 PBS




K5094 PBS




K5334 PBS




K5332 PBS




K5333 PBS



K5334 PBS



K5346 PBS



K5352 PBS

K5340 PBS
K5340 PBS B
3 PIN SOCKET OUTLET
WITH TELEPHONE SYMBOL
SINGLE OUTLET

1
1

K182 PBS
EURO 2 MODULE
K184 PBS
EURO 4 MODULE

5
5

K172 PBS
LJU6C 2 MODULE

5

K5091 PBS
1 GANG
ONE MODULE

1

K5092 PBS
1 GANG
TWO MODULE

1

K5093 PBS
2 GANG
THREE MODULE

1

K5094 PBS
2 GANG
FOUR MODULE

1

K5331 PBS
1 MODULE

1

K5332 PBS
2 MODULE

1

K5333 PBS
3 MODULE

1

K5334 PBS
4 MODULE

1

K5346 PBS
6 MODULE

1

K5348 PBS
8 MODULE

1

K5352 PBS
12 MODULE

1

MOUNTING BOXES

 FLUSH:
861 ZIC

 Accepts standard BS.546
2 amp 2 pin + earth plug where
2 pins are used for telephone
circuits and the earth pin is used
to ensure correct polarity.

 DIMENSIONS:
87.5 x 87.5mm

 FIXING CENTRES:
60.3mm

BS.546: 1950

MOUNTING BOXES

 Suitable for flush boxes to
BS.4662: 1970 and surface boxes
to BS.5733: 1995.

 Refer to appropriate data modules
for minimum box depth.

 See pages 139-140 and 156-158
for complete data module selection.

 FIXING CENTRES
1 gang: 60.3mm
2 gang: 120.6mm

 BS.5733: 1995
where applicable

MOUNTING BOXES

 Suitable for flush boxes to
BS.4662: 1970 and surface boxes
to BS.5733: 1995.

 Refer to appropriate data modules
for minimum box depth.

 See pages 139-140 and 156-158
for complete data module selection.

 FIXING CENTRES
1 gang: 60.3mm
2 gang: 120.6mm

 BS.5733: 1995
where applicable

MOUNTING BOXES

 FLUSH 35mm
(for extra wiring space)
1 GANG: 866 ZIC
2 GANG: 886 ZIC

 See Pages 140 and 261 for
appropriate data modules and
mounting frames

 DIMENSIONS:
1 gang: 87.5 x 87.5mm
2 gang: 87.5 x 149.5mm

 BS.5733: 1995
where applicable

 FIXING CENTRES
1 gang: 60.3mm
2 gang: 120.6mm

 BS.5733: 1995
where applicable

DIMENSIONS:

1 & 2 module: 87.5 x 87.5mm

3 & 4 module: 87.5 x 149.5mm

6 & 8 module: 146 x 146mm

12 module: 206 x 146mm

 See pages 247-249 for the
appropriate switch modules.

BS.5733: 1995

B suffix on the list number
denotes BLACK INSERTS