



LONG LIFE AXIAL FANS - IPX4 MINI





LONG LIFE AXIAL FANS - IPX4 MINI

- Axial fans to extract air and fumes directly outside.
- Can be wall, ceiling and panel mounted.
- Grille made in shining ABS material.
- Motor with ball bearings.
- In accordance with EN 60335-2-80.



• **Mini T** - With electronic timer adjustable from 2 to 20 minutes approx.

• **Mini Sensor** - The fan starts automatically when the infrared sensor detects a presence in the room. When the room is vacated the timer takes control keeping the fan operating for a preset time.

• Operates in either in the light or in the dark with a radius of 8 metres.

• Thanks to its completely automatic functioning is particularly suitable for rooms used by the general public.

Dimensions



CE



IPX4

Model	A	B	C	D	E
Mini 10 / 10 T / 10 Sensor	154	154	45	36	∅ 98
Mini 12 / 12 T / 12 Sensor	174	174	45	36	∅ 118



Splashproof fans for areas with high humidity.



Mini T and Sensor, easy timer adjustment by small control knob.

Mini Sensor, it is extremely simple to install since it is connected to the electrical system with just two wires, thus eliminating the connections that normally need to be made to the light and the light switch.



Threaded spigot to allow panel mounting by locking ring.
(See accessories page 108).

Technical Data

Model	Ref.	Hole diameter mm	Flow rate m ³ /h	W	Nominal voltage and frequency	Max pressure mm H ₂ O	dB (A) at 3 m	Weight kg
MINI 10	OW 137 2	100	85	14	220-240V 50Hz	2,8	38	0,5
MINI 12	OW 138 0	120	125	21	220-240V 50Hz	4	39	0,65
MINI 10 T	OW 141 4	100	85	14	220-240V 50Hz	2,8	38	0,5
MINI 12 T	OW 142 2	120	125	21	220-240V 50Hz	4	39	0,65
MINI 10 SENSOR	OW 121 6	100	85	14	220-240V 50Hz	2,8	38	0,5
MINI 12 SENSOR	OW 122 4	120	125	21	220-240V 50Hz	4	39	0,65